

Cruiser/Touring/Custom

Venom

- Low noise levels
- Long life
- Excellent cornering stability
- Large range of sizes
- Reinforced fitments available for bikes carrying heavy loads
- Availability of whitewalls in some sizes

Long distance touring and hauling heavy loads? You need Avon Venom, tyres developed with a tread pattern to produce low noise levels – essential on long journeys. Thanks to innovative carcass construction and tread rubber formulation, the Venom is what's known as a low-rolling resistance tyre – this means it has long life characteristics and reduces fuel consumption. These tyres are very stable through corners and give progressive (and therefore reassuring) turn-in. Finally, because some cruisers and tourers carry bigger loads than others, the Venom is available in a range of reinforced sizes.

Venom specification								
Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/ inches	Overall Diameter mm/ inches	Depth mm	Revs per km/mile
Venom AM41 Front								
2808012	80/90-21	48H	MT1.85	1.60 – 2.15	83/3.3	688/27.1	5.2	479/766.4
2808112	90/90-21	54H	MT2.15	1.85 – 2.50	94/3.7	701/27.6	5.2	468/748.8
2806912	100/90-18	56H	MT2.50	2.15 – 2.75	107/4.2	638/25.1	5.2	520/832.0
2809012	100/90-19	57H	MT2.50	2.15 – 2.75	109/4.3	662/26.1	5.2	500/800.0
2809019	100/90-19 _{ww}	57H	MT2.50	2.15 – 2.75	110/4.3	662/26.1	5.2	500/800.0
2809612	110/90-19	62H	MT2.50	2.15 – 3.00	119/4.7	682/26.9	5.2	487/779.2
2806012	120/90-18*	71H	MT2.75	2.50 – 3.00	129/5.1	674/26.5	5.2	496/793.6
2804112	120/70-21	62H	MT3.50	2.75 – 3.75	120/4.7	709/27.9	4.8	467/747.3
2806612	130/70B18*	69H	MT3.50	3.00 – 4.00	130/5.1	647/25.5	4.7	513/820.8
2809713	140/70B18	67V	MT3.75	3.00 – 4.50	139/5.5	658/25.9	4.7	503/805.2
2807412	150/80-16	71H	MT3.50	3.00 – 4.00	157/6.2	637/25.1	5.2	525/840.0
2809312	MH90-21*	56H	MT1.85	1.60 – 2.15	83/3.3	688/27.1	5.2	479/766.4
2809319	MH90-21 _{ww} *	56H	MT1.85	1.60 – 2.15	83/3.3	686/27.0	5.2	479/766.4
2805012	MT90B16*	74H	3.00D	2.50 – 3.50	136/5.4	638/25.1	5.2	523/836.8
2805017	MT90B16 _{nw} *	74H	3.00D	2.50 – 3.50	136/5.4	638/25.1	5.2	523/836.8
2805019	MT90B16 _{ww} *	74H	3.00D	2.50 – 3.50	136/5.4	638/25.1	5.2	523/836.8



Venom AM42 Rear								
2848712	140/90B16*	77H	MT3.50	2.75 – 3.75	143/5.6	649/25.6	8.7	518/828.8
2848719	140/90B16 _{ww}	77H	MT3.50	2.75 – 3.75	143/5.6	649/25.6	8.7	518/828.8
2844412	140/90-15*	76H	MT3.50	2.75 – 3.75	149/5.9	633/24.9	8.7	530/848.0
2847493	150/80B16*	77V	MT3.50	3.00 – 4.25	157/6.2	640/25.2	7.2	518/828.8
2847492	150/80B16*	77H	MT3.50	3.00 – 4.25	150/5.9	641/25.2	8.7	518/828.8
2957412	150/80B16 _{ww}	77V	MT3.50	3.00 – 4.25	157/6.2	641/25.2	7.2	518/828.8
2848912	150/90B15*	80H	MT3.50	3.00 – 4.25	159/6.3	645/25.4	8.7	523/836.8
2848913	150/90B15	74V	MT3.50	3.00 – 4.25	159/6.3	645/25.4	8.7	523/836.8
2846513	150/70B18	70V	MT4.25	3.00 – 4.50	148/5.8	665/26.2	5.7	498/796.7
2844912	160/80B16*	81H	MT4.00	3.50 – 4.50	167/6.6	665/26.2	8.7	505/808.0
2844512	170/80B15*	83H	MT4.00	3.50 – 4.50	176/6.9	659/25.9	8.7	512/819.2
2843712	200/70-15*	82H	MT5.5	5.50 – 6.50	203/8.0	665/26.2	7.7	505/808.0
2845012	MT90B16*	74H	3.00D	2.50 – 3.50	133/5.2	638/25.1	8.7	522/835.2
2845017	MT90B16 _{nw} *	74H	3.00D	2.50 – 3.50	131/5.2	640/25.2	8.7	522/835.2
2845019	MT90B16 _{ww} *	74H	3.00D	2.50 – 3.50	134/5.3	639/25.2	8.7	522/835.2

WW – Wide White Wall. NW – Narrow White Wall.

* Reinforced.

MT90-16 replaces 130/90-16. 140/90B16 replaces MU85B16.

