

## Custom

# Venom-R

- Includes Avon's widest custom tyre
- Aggressive tread design
- Sizes to fit custom motorcycles



## Cruiser/Touring/Custom

# AM20/AM21

- Accomplished all-rounder
- Tread pattern designed to give first class water dispersal under the contact patch.

Venom-R		specification						
Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
<b>Venom-R AM42 Rear</b>								
4953913	180/55R18	74V	MT5.5	5.50 - 6.00	177 / 7.0	662 / 26.1	7.0	500 / 800.3
4952712	300/40R17	90V	MT10.5	10.00 - 11.00	299 / 11.8	668 / 26.3	6.5	496 / 793.1
4955413	330/30R17	87V	MT12.0	11.00 - 12.50	330 / 12.9	634 / 25.0	6.5	522 / 835.6

AM20/AM21		specification						
Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
<b>AM20 Front</b>								
2748812	90/90-19	52H	MT2.15	1.85 - 2.50	95 / 3.7	647 / 25.5	5.0	512 / 819.2
2748112	90/90-21	54H	MT2.15	1.85 - 2.50	93 / 3.7	700 / 27.6	5.0	474 / 758.4
2745012	130/90-16*	73H	3.00D	2.50 - 3.50	138 / 5.4	638 / 25.1	5.0	525 / 840.0

AM21 Rear		specification						
Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
2755019	MT90-16*	74H	3.00D	2.50 - 3.50	139 / 5.5	650 / 25.4	7.8	517 / 827.2
2759012	230/60B15	86H	MT6.25	5.50 - 7.00	230 / 9.1	658 / 25.9	8.6	508 / 812.8

\* Reinforced.  
Equivalent MT90-16 = 130/90-16.