

## Classic

# Speedmaster MKII (AM6)

- Classic ribbed front tyre
- Speed rated to 112 mph/180kmh
- Curved tread profile and ribbed pattern so typical of classic bikes
- Best used in conjunction with the Safety Mileage MKII rear tyre



**Speedmaster MKII**



**Sidecar Triple Duty Universal**

## Classic

# Safety Mileage MKII (AM7)

- Classic block pattern rear tyre
- Available in a variety of different tread patterns designed to suit older bikes
- Modern rubber compounds deliver enhanced durability and performance
- Best used in conjunction with the Speedmaster MKII front tyre



**Safety Mileage MKII**



**Safety Mileage MKII (4.00-19)**



**Safety Mileage MKII (5.00-16)**

## Classic

# Sidecar Triple Duty

- A great all-rounder for every position
- Although especially suited to the front wheel, these tyres can be used in any position on a sidecar outfit

## AM6/AM7 / Sidecar Triple specification

| Code                   | Tyre Size  | Service Index | Rec Rim | Rim min-max | Overall Width mm/inches | Overall Diameter mm/inches | Depth mm | Revs per km/mile |
|------------------------|------------|---------------|---------|-------------|-------------------------|----------------------------|----------|------------------|
| <b>Speedmaster AM6</b> |            |               |         |             |                         |                            |          |                  |
| 1727410                | 300-19 TT* | 54S           | 1.85    | 1.60 - 2.15 | 78 / 3.1                | 641 / 25.2                 | 3.5      | 517 / 827.2      |
| 1658410                | 300-20 TT  | 50S           | 1.85    | 1.60 - 2.15 | 75 / 3.0                | 665 / 26.2                 | 3.5      | 498 / 796.7      |
| 1659401                | 300-21 TT* | 57S           | 1.85    | 1.60 - 2.15 | 76 / 3.0                | 691 / 27.2                 | 3.6      | 481 / 769.6      |
| 1657501                | 325-19 TT  | 54S           | 2.15    | 1.85 - 2.50 | 86 / 3.4                | 658 / 25.9                 | 4.0      | 497 / 795.2      |
| 1657601                | 350-19 TT  | 57S           | 2.15    | 1.85 - 2.50 | 92 / 3.6                | 682 / 26.9                 | 3.6      | 482 / 771.2      |
| 1655501                | 3.25-17 TT | 50S           | 2.15    | 1.85 - 2.50 | 89 / 3.5                | 616 / 24.3                 | 3.5      | 538 / 860.1      |

|                                 |            |     |       |             |           |            |     |             |
|---------------------------------|------------|-----|-------|-------------|-----------|------------|-----|-------------|
| <b>Safety Mileage MK II AM7</b> |            |     |       |             |           |            |     |             |
| 1727610                         | 350-19 TT  | 57S | 2.15  | 1.85 - 2.50 | 93 / 3.7  | 682 / 26.9 | 8.1 | 482 / 771.2 |
| 1646801                         | 400-18 TT  | 64S | 2.50  | 2.15 - 3.00 | 111 / 4.4 | 677 / 26.7 | 8.1 | 488 / 780.8 |
| 1647801                         | 400-19 TT  | 65S | 2.50  | 2.15 - 3.00 | 110 / 4.3 | 702 / 27.6 | 9.2 | 471 / 753.6 |
| 1694901                         | 500-16 TT  | 69S | 3.00D | 3.00 - 3.50 | 131 / 5.2 | 669 / 26.3 | 8.1 | 499 / 798.4 |
| 1645501                         | 3.25-17 TT | 50S | 2.15  | 1.85 - 2.50 | 89 / 3.5  | 616 / 24.3 | 3.5 | 538 / 860.1 |

|                            |           |     |      |             |          |            |     |             |
|----------------------------|-----------|-----|------|-------------|----------|------------|-----|-------------|
| <b>Sidecar Triple Duty</b> |           |     |      |             |          |            |     |             |
| 1697605                    | 350-19 TT | 57L | 2.15 | 1.85 - 2.50 | 92 / 3.6 | 679 / 26.7 | 9.4 | 491 / 785.6 |

TT - Tube Type. \* Reinforced.