SAFETY DATA SHEET

1. Product and company identification

Product name Bel-Ray EXS Synthetic Ester 4T Engine Oil 10W-50

Product code 99160 SDS number 6921

Bel-Ray Company, LLC

GPO Box 2650 Sydney, NSW 1171 PO Box 526 Farmingdale N.J. 07727

1 732-938-2421

CHEMTREC: 1800 069 100 (AUS)

Bel-Ray Company, LLC

P.O. Box 526

Farmingdale, NJ 07727 **United States of America**

+1 732 938 2421

CHEMTREC: 800-424-9300 (USA)

CHEMTREC: +1 703-527-3887 (outside USA - call collect)

Recommended use and Limitations on use

Recommended use 4T Motorcycle Engine Oil

2. Hazards identification

GHS classification

Physical hazards Not classified. Health hazards Not classified.

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Label elements

None. **Symbols** Signal word None.

Harmful to aquatic life. **Hazard statement**

Precautionary statement

Prevention Keep out of reach of children. Read label before use. Avoid release to the environment.

Response If medical advice is needed, have product container or label at hand.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information 89.61 % of the mixture consists of component(s) of unknown acute hazards to the aquatic

environment.

3. Composition/information on ingredients

Substance or mixture Mixture

Chemical property	CAS Number	Concentration (%)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	0 - < 20
Distillates (petroleum), Hydrotreated Heavy Naphthenic		
Other components below reportable levels		90 - 100

4. First aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Material name: Bel-Ray EXS Synthetic Ester 4T Engine Oil 10W-50 99160 Version No.: 5.0 Revision date: 09-May-2016 Print date: 09-May-2016 1/6

SDS NEW ZEALAND

Potential delayed effects

Direct contact with eyes may cause temporary irritation.

Personal protection for first-aid responders

Not available.

Notes to physician Treat symptomatically.

5. Fire-fighting measures

Extinguishing media Water fog.

Extinguishing media to avoid Do not use water jet as an extinguisher, as this will spread the fire.

HAZCHEM Code Number

Specific hazards during fire

fighting

During fire, gases hazardous to health may be formed.

Special fire fighting

procedures

Not available.

Protection of fire-fighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Wear

suitable protective equipment.

Hazards from combustion

products

May include oxides of Nitrogen.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Spill cleanup methods

This product is miscible in water. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Handling

Precautions Avoid release to the environment.

Safe handling advice Avoid prolonged exposure. Observe good industrial hygiene practices. Use personal protection

recommended in Section 8 of the SDS.

Prevention of fire and

explosion

No specific recommendations.

Local and general ventilation

Provide adequate ventilation.

Storage

Suitable storage conditions

Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the

SDS).

Incompatible materials

For further information, please refer to section 10.

Safe packaging materials Store in original tightly closed container.

8. Exposure controls/personal protection

Exposure limits

New Zealand. WES. (Workplace Exposure Standards)

Components	Туре	Value	Form	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	

Material name: Bel-Ray EXS Synthetic Ester 4T Engine Oil 10W-50

SDS NEW ZEALAND 99160 Version No.: 5.0 Revision date: 09-May-2016 Print date: 09-May-2016

ACGIH Value **Form** Components Type Inhalable fraction. Distillates (petroleum), TWA 5 mg/m3 hydrotreated heavy naphthenic (CAS

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A) Components **Type** Value

Distillates (petroleum), **TWA** hydrotreated heavy naphthenic (CAS

Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational

Environment)

64742-52-5)

64742-52-5)

64742-52-5)

Form Components **Type** Value Distillates (petroleum), TWA Mist. 5 mg/m3 hydrotreated heavy naphthenic (CAS

Biological limit values No biological exposure limits noted for the ingredient(s).

Engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should

be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure

5 mg/m3

limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Skin protection Wear suitable protective clothing.

Eye/face protection Wear safety glasses with side shields (or goggles).

Radioactive or thermal

hazards

Follow standard monitoring procedures.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance Oily. Liquid. Physical state Liquid. **Form** Liquid. Colour Amber. Odour Petroleum **Odour threshold** Not available. Not available. Melting point/freezing point Not available.

Boiling point, initial boiling

> 250 °C (> 482 °F)

point, and boiling range

Flash point 222.0 °C (431.6 °F) Pensky-Martens Closed Cup

260 °C (500 °F) estimated **Auto-ignition temperature**

Flammability (solid, gas) Not applicable. Flammability limit - lower Not available.

(%)

Not available.

Flammability limit - upper

Explosive limit - lower (%) Not available. Explosive limit - upper

Not available.

99160 Version No.: 5.0 Revision date: 09-May-2016 Print date: 09-May-2016

(%)

Vapour pressure 0.000002 hPa estimated

Density 854.00 kg/m3

Material name: Bel-Ray EXS Synthetic Ester 4T Engine Oil 10W-50 SDS NEW ZEALAND Vapour density Not available. **Evaporation rate** Not available. Relative density Not available.

Solubility(ies)

Solubility (water) Negligible

Hydrocarbon Solvents Solubility (other)

Oil

Partition coefficient (n-octanol/water)

Not available.

Decomposition temperature Not available.

Viscosity 120.8 cSt ASTM D445

Viscosity temperature 40 °C (104 °F) Percent volatile 0.08 % estimated

Other data

Explosive properties Not explosive. **Oxidising properties** Not oxidising.

Specific gravity 0.87 VOC < 1 %

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Stability Material is stable under normal conditions. Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition Nitrogen oxides (NOx). At thermal decomposition temperatures, carbon monoxide and carbon

products dioxide.

Possibility of hazardous No dangerous reaction known under conditions of normal use.

reactions

11. Toxicological information

Information on likely routes of exposure

Ingestion Expected to be a low ingestion hazard. Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. **Eve contact** Direct contact with eyes may cause temporary irritation.

Product Test results

Bel-Ray EXS Synthetic Ester 4T Engine Oil 10W-50

Acute Dermal

LD50 Rabbit 27322 mg/kg estimated

Inhalation

LC50 Rat 1545 mg/l, 4 hours estimated

Oral

LD50 Rat 6702 mg/kg estimated

Routes of exposure Inhalation.

Symptoms Direct contact with eyes may cause temporary irritation. Skin corrosion/irritation Based on available data, the classification criteria are not met. Direct contact with eyes may cause temporary irritation. Serious eye damage/eye

irritation

Not a respiratory sensitizer. Respiratory sensitiser

Skin sensitiser Not applicable.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Material name: Bel-Ray EXS Synthetic Ester 4T Engine Oil 10W-50 SDS NEW ZEALAND 99160 Version No.: 5.0 Revision date: 09-May-2016 Print date: 09-May-2016 4/6

^{*} Estimates for product may be based on additional component data not shown.

Carcinogenicity Due to lack of data the classification is not possible.

Toxic to reproduction This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure

Not classified.

Specific target organ toxicity - repeated

Due to lack of data the classification is not possible.

exposure

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

Relevant negative data Not available.

12. Ecological information

Ecotoxicological data

Product Test results Species

Bel-Ray EXS Synthetic Ester 4T Engine Oil 10W-50

Aquatic

EC50 Crustacea Daphnia 29696.9688 mg/l, 48 hours estimated

Harmful to aquatic life. **Ecotoxicity**

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulation No data available. Partition coefficient Not available.

n-octanol/water (log Kow)

Bioconcentration factor (BCF) Not available.

Mobility This product is miscible in water.

Other hazardous effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal

methods/information

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Special precautions Dispose in accordance with all applicable regulations.

14. Transport information

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established. Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

Applicable regulations

New Zealand Inventory of Chemicals (NZIoC): Registration status

Distillates (petroleum), hydrotreated heavy naphthenic May be used as a single component chemical under an appropriate (CAS 64742-52-5) group standard

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No

Material name: Bel-Ray EXS Synthetic Ester 4T Engine Oil 10W-50 SDS NEW 7FALAND

^{*} Estimates for product may be based on additional component data not shown.

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

References Not available.

Issued by

Not available.

Prepared by

Not available.

Disclaimer Bel-Ray Company, LLC cannot anticipate all conditions under which this information and its product,

or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

Issue date 13-January-2011 **Revision date** 09-May-2016

Revision information This document has undergone significant changes and should be reviewed in its entirety

Material name: Bel-Ray EXS Synthetic Ester 4T Engine Oil 10W-50 SDS NEW ZEALAND 99160 Version No.: 5.0 Revision date: 09-May-2016 Print date: 09-May-2016 6/6