SAFETY DATA SHEET

1. Product and company identification

Product name V-Twin Semi-Synthetic Engine Oil 20W-50

Product code 96910 SDS number 7137

Bel-Ray Company, LLC

GPO Box 2650 Sydney, NSW 1171 PO Box 526 Farmingdale N.J. 07727

1 732-938-2421

CHEMTREC: 1800 069 100 (AUS)

Bel-Ray Company, LLC

P.O. Box 526

Farmingdale, NJ 07727 **United States of America**

+1 732 938 2421

CHEMTREC: 800-424-9300 (USA)

CHEMTREC: +1 703-527-3887 (outside USA - call collect)

Recommended use and Limitations on use

Recommended use Engine oil

2. Hazards identification

GHS classification

Physical hazards Not classified. Health hazards Not classified.

Environmental hazards Hazardous to the aquatic environment, acute Category 2

Hazardous to the aquatic environment, Category 3

long-term hazard

Label elements

Symbols None. Signal word None.

Hazard statement Harmful to aquatic life.

Precautionary statement

Prevention Keep out of reach of children. Read label before use. Avoid release to the environment.

If medical advice is needed, have product container or label at hand. Response

Storage Store away from incompatible materials.

Disposal Dispose of contents/container to

Supplemental information None.

3. Composition/information on ingredients

Substance or mixture Mixture

CAS Number Chemical property Concentration (%) 64741-88-4 0 - < 90 Distillates (petroleum), solvent-refined heavy paraffinic Distillates (petroleum), Solvent-refined Heavy Paraffinic Other components below reportable levels 70 - < 80

4. First aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Material name: V-Twin Semi-Synthetic Engine Oil 20W-50 SDS NEW ZEALAND Ingestion Rinse mouth. Do not induce vomiting. Get medical attention if symptoms occur. Never give liquid to

an unconscious person.

Potential delayed effects

Irritation of eyes and mucous membranes. Skin irritation. Personal protection for

first-aid responders

Not available.

Not available.

Notes to physician Provide general supportive measures and treat symptomatically.

5. Fire-fighting measures

Extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Extinguishing media to avoid Do not use water jet as an extinguisher, as this will spread the fire.

HAZCHEM Code Number

Specific hazards during fire

fighting

During fire, gases hazardous to health may be formed.

Special fire fighting

procedures

Wear suitable protective equipment. Self-contained breathing apparatus and full protective clothing

must be worn in case of fire.

Hazards from combustion

Protection of fire-fighters

products

May include oxides of Nitrogen. Carbon monoxide and carbon dioxide.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

Spill cleanup methods

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapours or divert vapour cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Handling

Precautions Avoid release to the environment.

Safe handling advice Observe good industrial hygiene practices. Use personal protection recommended in Section 8 of

the SDS.

Prevention of fire and

explosion

No specific recommendations.

Local and general ventilation

Provide adequate ventilation.

Storage

Suitable storage conditions

Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the

SDS).

Incompatible materials

For further information, please refer to section 10.

Store in original tightly closed container. Safe packaging materials

Material name: V-Twin Semi-Synthetic Engine Oil 20W-50 SDS NEW ZEALAND 96910 Version No.: 4.0 Revision date: 28-May-2016 Print date: 28-May-2016

8. Exposure controls/personal protection

Exposure limits

New Zealand. WES. (Workplace Exposure Standards)

Components	Туре	Value	Form	
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A) Components Value **Type**

Distillates (petroleum), TWA 5 mg/m3 solvent-refined heavy

paraffinic (CAS 64741-88-4)

Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational

Environment)

Components Value **Form Type** Distillates (petroleum), TWA 5 mg/m3 Mist. solvent-refined heavy

paraffinic (CAS 64741-88-4)

Biological limit values No biological exposure limits noted for the ingredient(s).

Engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should

be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure

limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection Wear appropriate chemical resistant gloves.

Skin protection Wear suitable protective clothing.

Eye/face protection Wear safety glasses with side shields (or goggles).

Radioactive or thermal

hazards

Follow standard monitoring procedures.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance Oily. Liquid. Physical state Liquid. **Form** Liquid. Colour Amber. Odour Petroleum **Odour threshold** Not available. Not available. pН

Melting point/freezing point Boiling point, initial boiling

Not available.

point, and boiling range

> 296 °C (> 564.8 °F)

218.0 °C (424.4 °F) Pensky-Martens Closed Cup

Auto-ignition temperature 260 °C (500 °F) estimated

Flammability (solid, gas) Not available. Flammability limit - lower (%)

1 % estimated

Flammability limit - upper

Explosive limit - lower (%)

50 % estimated

(%)

Not available.

Explosive limit - upper (%)

Flash point

Not available.

0.000002 hPa estimated Vapour pressure

Material name: V-Twin Semi-Synthetic Engine Oil 20W-50 96910 Version No.: 4.0 Revision date: 28-May-2016 Print date: 28-May-2016 Density888.00 kg/m3Vapour densityNot available.Evaporation rateNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Negligible
Solubility (other) Oil

Partition coefficient (n-octanol/water)

Not available.

Decomposition temperature

ture Not available.

Viscosity 177.3 cSt ASTM D445

Viscosity temperature 40 °C (104 °F)

Percent volatile 0.03 % estimated

Other data

Specific gravity 0.89 VOC < 1 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Stability Material is stable under normal conditions. **Conditions to avoid** Contact with incompatible materials.

Incompatible materials Strong oxidising agents.

Nitrona and Mo

Hazardous decomposition products

Nitrogen oxides (NOx). At thermal decomposition temperatures, carbon monoxide and carbon

dioxide.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

11. Toxicological information

Information on likely routes of exposure

Ingestion Expected to be a low ingestion hazard.

InhalationNo adverse effects due to inhalation are expected.Skin contactNo adverse effects due to skin contact are expected.Eye contactDirect contact with eyes may cause temporary irritation.

Product Species Test results

V-Twin Semi-Synthetic Engine Oil 20W-50

<u>Acute</u> Dermal

LD50 Rabbit 2958 mg/kg estimated

Inhalation

LC50 Rat 1545 mg/l, 4 hours estimated

Oral

LD50 Rat 2963 mg/kg estimated

Routes of exposure Inhalation. Eye contact.

Symptoms Irritation of eyes and mucous membranes. Skin irritation.

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye Based on available data, the classification criteria are not met.

irritation

Respiratory sensitiser

Skin sensitiser

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Material name: V-Twin Semi-Synthetic Engine Oil 20W-50 SDS NEW ZEALAND

^{*} Estimates for product may be based on additional component data not shown.

Specific target organ toxicity - single exposure Based on available data, the classification criteria are not met.

Specific target organ

toxicity - repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Not an aspiration hazard.

Not available. **Chronic effects** Relevant negative data Not available.

12. Ecological information

Ecotoxicological data

Product	Species		Test results	
V-Twin Semi-Synthetic	c Engine Oil 20W-5	0		
Aquatic				
Crustacea	EC50	Daphnia	29696.9688 mg/l, 48 hours estimated	
Fish	LC50	Fish	168.3641 mg/l, 96 hours estimated	

^{*} Estimates for product may be based on additional component data not shown.

Harmful to aquatic life. **Ecotoxicity**

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulation No data available. Partition coefficient Not available.

n-octanol/water (log Kow)

Bioconcentration factor (BCF) Not available.

Mobility This product is miscible in water.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other hazardous effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal methods/information

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

14. Transport information

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

Applicable regulations

New Zealand Inventory of Chemicals (NZIoC): Registration status

Distillates (petroleum), solvent-refined heavy paraffinic May be used as a single component chemical under an appropriate (CAS 64741-88-4) group standard

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes

SDS NEW ZEALAND 96910 Version No.: 4.0 Revision date: 28-May-2016 Print date: 28-May-2016

Inventory name Country(s) or region On inventory (yes/no)* European List of Notified Chemical Substances (ELINCS) Europe Japan Inventory of Existing and New Chemical Substances (ENCS) No Existing Chemicals List (ECL) Korea Yes New Zealand New Zealand Inventory No **Philippines** Philippine Inventory of Chemicals and Chemical Substances Yes (PICCS)

Toxic Substances Control Act (TSCA) Inventory

16. Other information

United States & Puerto Rico

References Not available.

Issued by

Not available.

Prepared by

Not available. **Disclaimer**

Bel-Ray Company, LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Issue date11-January-2012Revision date28-May-2016

Revision information This document has undergone significant changes and should be reviewed in its entirety

Material name: V-Twin Semi-Synthetic Engine Oil 20W-50 SDS NEW ZEALAND

Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).