

SPECTRO LUBRICANT TECHNICAL DATA

Spectro 4 Engine Lubricant



- EXCEPTIONALLY HIGH ANTI-WEAR ADDITIVE TREATMENT REDUCES WEAR.
- EXTENDS COMPONENT LIFE.
- TREMENDOUS LUBRICATION PROTECTION IN EXTREME HEAT CONDITIONS.
- PROVIDES SMOOTHER SHIFTING.
- EXCEPTIONAL OFF-SEASON PROTECTION OF INTERNAL PARTS
- API SL/ JASO MA

Description

Spectro 4 is the ultimate petroleum motor lubricant formulated specifically for use in high performance engines. It incorporates a blend of the worlds leading high V.I. petroleum base oils and the most advanced anti-wear additive system available for motorcycles.

Meets all known OEM warranty requirements.

Application

Spectro 4 should be used according to the manufacturer's recommended change intervals and viscosity. If no viscosity is recommended, use the 10w40.

For Racing Use

Spectro 4 motor oil is formulated specifically for use in all racing and high performance / street applications.

Typical Inspections	10w40	20w50	20w40
Kinematic Viscosity @ 100° C cSt	14.3	18.6	14.6
Kinematic Viscosity @ 40° C cSt	97.2	158	133
Flash Point, °C	216	230	220
Pourpoint, °C	-29	-18	-23
Viscosity Index	155	132	122

Code	Description	Weight
L.S41040	12/1 Liter Bottles	25 Lbs.
L.S42040	12/1 Liter Bottles	25 Lbs.
L.S42050	12/1 Liter Bottles	25 Lbs.
U.S41040	4/4 Liter Bottles	35 Lbs.
U.S42050	4/4 Liter Bottles	35 Lbs.
Z.S41040	1/55 Gallon Drum	450 Lbs.
Z.S42050	1/55 Gallon Drum	450 Lbs.

SPECTRO OILS OF AMERICA
993 Federal Rd., Brookfield, CT 06804
203-775-1291 Fax 203-775-8720
www.spectro-oils.com

