

Material Safety Data Sheet

SECTION 1 IDENTIFICATION

Product Name: SPECTRO Foam Filter Cleaner

Manufacturer:
Intercontinental Lubricants Corp./
Spectro Oils of America
993 Federal Road
Brookfield, CT 06804
(203) 775-1291 Fax: (203) 775-8720

MSDS Date of Preparation: 7/14/04

SECTION 2 PRODUCT COMPONENTS

<u>INGREDIENTS</u>	<u>CAS#.</u>	<u>WT. %</u>	<u>EXPOSURE LIMITS</u>
Aliphatic Petroleum Distillates	64742-47-8	40-50%	100 ppm TWA (manufacture)
2-Butoxyethanol	111-76-2	10-20%	50 ppm TWA skin (OSHA) 20 ppm TWA (ACGIH)
Xylene	1330-20-7	10-20%	100 ppm TWA (OSHA/ACGIH) 150 ppm STEL (ACGIH)
Ethylbenzene	100-41-4	1-5%	100 ppm TWA (OSHA/ACGIH) 125 ppm STEL (ACGIH)
Liquefied Petroleum Gas	68476-85-7	15-20%	1,000 ppm TWA (OSHA) 1,000 ppm TWA (ACGIH) (as aliphatic hydrocarbon gas)

SECTION 3: HAZARDS IDENTIFICATION EMERGENCY OVERVIEW

This product is a clear, colorless liquid with a mild aromatic odor. Flammable aerosol (Flash Point 80°F). May cause eye and skin irritation. May be absorbed through the skin in harmful amounts. Breathing vapors may cause respiratory irritation and central nervous system effects including headache, dizziness, nausea, confusion and coma. Accidental ingestion may cause gastrointestinal effects with irritation, nausea, vomiting, dizziness, coma and death. Aspiration into the lungs during ingestion or vomiting may cause lung damage.

HEALTH HAZARDS:

INHALATION: Excessive inhalation of vapors or mists may cause upper respiratory tract irritation and central nervous system effects including headache, nausea, dizziness, drowsiness, weakness, confusion, unconsciousness and coma. At very high concentrations, the propellant has been reported to possibly produce heart rhythm irregularities due to sensitization of the heart to adrenaline.

SKIN CONTACT: May cause irritation. 2-Butoxyethanol may be absorbed through the skin possibly resulting in symptoms similar to those listed under inhalation.

EYE CONTACT: May cause moderate irritation.

INGESTION: Unlikely due to aerosol container. Swallowing may cause gastrointestinal disturbances including abdominal pain, belching, nausea, vomiting, dizziness, drowsiness, coma or death. May cause central nervous system depression with unsteady gait and sedation. Aspiration into the lungs may occur during ingestion or vomiting may cause lung damage. Kidney and liver damage may also occur.

SECTION 3: HAZARDS IDENTIFICATION (continued)

CHRONIC EFFECTS OF OVEREXPOSURE: Prolonged overexposure to 2-butoxyethanol may cause blood, liver and kidney damage. Prolonged overexposure to xylene may cause liver and kidney damage. Prolonged skin exposure may cause dermatitis. Intentional misuse by deliberately concentrating and inhaling the product may be harmful or fatal.

CARCINOGENICITY: Ethyl benzene is listed as possibly carcinogenic to humans (Group 2B) by IARC.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Individuals with chronic skin and nervous system disorders may be at increased risk from exposure to this material. Breathing of vapor and/or mist may aggravate respiratory disorders.

SECTION 4 EMERGENCY and FIRST AID PROCEDURES

EYE CONTACT: Immediately flush eye with water for at least 15 minutes while lifting the upper and lower lids. Get medical attention.

SKIN CONTACT: Remove contaminated clothing immediately and launder before reuse. Wash thoroughly with soap and water. Get medical attention if irritation develops.

INHALATION: Remove victim to fresh air. If breathing has stopped give artificial respiration. If breathing is difficult have qualified personnel administer oxygen. Get medical attention.

INGESTION: Unlikely due to aerosol container. Do not induce vomiting. Rinse mouth out with water. Get immediate medical attention by calling a Poison Control Center or hospital emergency department.

SECTION 5 FIRE and EXPLOSION HAZARD DATA

FLASH POINT: 80°F/27°C

METHOD: TCC

FLAMMABLE LIMITS: (vol % in air) LEL: 1.0% UEL: 6.6%

AUTOIGNITION TEMPERATURE: Not established

AEROSOL PROTECTION LEVEL (NFPA 30B): Level 3

EXTINGUISHING MEDIA: Water spray, mist or fog. Cool fire exposed containers with water.

SPECIAL FIREFIGHTING PROCEDURES: Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus. Use shielding to protect against bursting cans.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Extremely flammable aerosol. Contents under pressure. Keep away from heat and open flames. Containers may rupture or explode at temperatures above 120°F.

SECTION 6 ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear appropriate protective equipment. Remove all sources of ignition. Ventilate area. Collect material for disposal using non-combustible absorbent material and place in a container suitable for flammable waste.

SECTION 7 HANDLING and STORAGE

Extremely Flammable Aerosol.

Avoid contact with eyes, skin and clothing. Avoid breathing vapors and mists. Use with adequate ventilation. Wash thoroughly after handling. Remove contaminated clothing and launder before re-use. No smoking in use or storage area. Shake can well before use.

SECTION 7 HANDLING and STORAGE (continued)

Protect containers from physical damage. Store in a cool, well ventilated area at temperatures below 120°F. Store away from direct sunlight. Do not puncture or incinerate containers.

Empty containers retain product residues. Do not cut, weld, braze, etc. on or near empty containers. Follow all MSDS precautions in handling empty containers.

SECTION 8 EXPOSURE CONTROLS and PERSONAL PROTECTION

RESPIRATORY PROTECTION: None needed under normal use conditions with adequate ventilation. If the TLV is exceeded use a NIOSH approved respirator with organic vapor cartridges and a particulate pre-filter (R or P series). For higher concentrations (greater than 10 times the TLV) a NIOSH approved supplied air respirator (with escape bottle if required) or self-contained breathing apparatus may be required. Selection of respiratory protection depends on the contaminant type, form and concentration. Select in accordance with OSHA 1910.134 and good Industrial Hygiene practice.

VENTILATION: Good general room ventilation (equivalent to outdoors) should be adequate under normal conditions. If the recommended exposure limit is exceeded, explosion-proof mechanical ventilation such as local exhaust may be required.

GLOVES: Teflon or other impervious gloves are recommended where prolonged or repeated skin contact is likely.

EYE PROTECTION: Safety glasses or goggles recommended.

OTHER PROTECTIVE EQUIPMENT: Impervious apron, boots and other clothing are recommended if needed to avoid prolonged/repeated skin contact. Suitable washing facilities should be available.

SECTION 9 PHYSICAL and CHEMICAL PROPERTIES

BOILING POINT (@ 760 mmHg): 279°F

SPECIFIC GRAVITY (H₂O=1): 0.7545

VAPOR PRESSURE (@ 70°F mm Hg): 2.4

EVAPORATION RATE (Butyl Acetate =1): <1

APPEARANCE AND ODOR: Clear, colorless liquid with an aromatic odor.

MELTING POINT: Not available

VOLATILE: 90%

(VAPOR DENSITY (AIR=1): >1

COEFFICIENT OF WATER/OIL: Not available

SECTION 10 STABILITY and REACTIVITY

STABILITY: This material is stable.

CONDITIONS TO AVOID: Avoid heat, sparks and open flames. Avoid exposure to temperatures above 120°F.

INCOMPATIBILITY: Strong oxidizing agents, acids and bases.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may yield carbon monoxide and carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

ACUTE TOXICITY VALUES:

Aliphatic Petroleum Distillates: LD50 Oral rat: >5 g/kg

2-Butoxyethanol: LD50 Oral rat: 470 mg/kg

LC50 Inhalation rat: 700 ppm/7 hr

LD50 Skin rabbit: 220 mg/kg

Xylene: LD50 Oral rat: 4300 mg/kg

LC50 Inhalation rat: 5000 ppm/4 hr

LD50 Skin rabbit: >1700 mg/kg

Ethyl Benzene: LD50 Oral rat: 5460 mg/kg

Liquefied Petroleum Gas No data available

SECTION 11 TOXICOLOGICAL INFORMATION (continued)

Ethyl benzene is listed as possibly carcinogenic to humans (Group 2B) by IARC. Certain aliphatic petroleum distillates have been found to cause skin cancer in lifetime skin painting studies in laboratory animals. None of the components are known to cause sensitization in animals or humans. Xylene has been found to cause adverse reproductive effects in laboratory animals at high doses.

SECTION 12: ECOLOGICAL INFORMATION

There is no ecotoxicity data available for this product at this time.

SECTION 13: DISPOSAL INFORMATION

WASTE DISPOSAL METHOD: This product is RCRA Hazardous Waste (Ignitable) if discarded in the purchased form. Dispose in accordance with federal, state and local regulations. Do not incinerate containers. Dispose in accordance with all local, state and federal regulations.

SECTION 14: TRANSPORTATION INFORMATION

DOT SHIPPING DESCRIPTION: Consumer Commodity, ORM-D
DOT HAZARD CLASSIFICATION: ORM-D
DOT LABELS REQUIRED (49CFR172.101): None
UN NUMBER: None

SECTION 15: REGULATORY INFORMATION

OSHA HAZARD CLASSIFICATION: Flammable, pressure hazard, irritant, toxic, target organ effects.

EPA SARA 302: This product does not contain chemicals regulated under SARA Section 302.

EPA SARA 311 HAZARD CLASSIFICATION: Acute health, chronic health, fire hazard, sudden pressure release.

EPA SARA 313: This product contains the following chemicals that are regulated under SARA Title III, section 313:

2-Butoxyethanol (glycol ether)	111-76-2	10-20%
Xylene	1330-20-7	10-20%
Ethylbenzene	100-41-4	1-5%

CERCLA Hazardous Substances (Section 103)/RQ: Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for the product, based on the RQ for Xylene (20%) of 100 lbs, is 500 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

WHMIS CLASSIFICATION: Class B-5, Flammable Aerosol; Class D-2, Subdivision A: Very toxic material causing other chronic effects.

EU CLASSIFICATION: Flammable, Harmful (Xn)

EU RISK AND SAFETY PHRASES: R10, R20/21/22, R38, S2, S24, S36/37, S51

TOXIC SUBSTANCES CONTROL ACT: All of the components of this product are listed on the TSCA inventory.

CALIFORNIA PROPOSITION 65: This product contains 1-5% ethylbenzene which is known to the State of California to cause cancer.

Canada: All of the components of this product are listed on the Canadian Domestic Substances List (DSL).

SECTION 15: REGULATORY INFORMATION (continued)

EEC EINECS: All of the ingredients are listed on the EINECS inventory.

Australia: All of the ingredients of this product are listed on the Australian Inventory of Chemical Substances.

SECTION 16: OTHER INFORMATION

NFPA Rating: Health: 1 Fire: 3 Reactivity: 0