Technical Data Sheet

PREMIUM GEAR OIL 80W-90

HIGH PERFORMANCE GEAR OIL

DESCRIPTION:

Mineral-based gear oil specifically formulated for use in motorcycles and ATVs. Robust, shear-stable formulation is designed for transmissions without wet-clutches, differentials with or without hypoid gears and shaft-drives. Proprietary shape combines the finest mineral base stocks with industry leading extreme pressure and anti-wear additives to ensure hardware protection and smooth shifting. Exceeds the requirements of API GL-5.

FEATURES & BENEFITS:

- Formulated specifically for use in motorcycles and ATVs
- Superior protection from wear, pitting and spalling
- Shear stable formula maintains viscosity and ensures smooth shifting
- Surface-active chemistry keeps surfaces free of corrosion, deposits and wear
- Exceeds API GL-5 specifications

APPLICATIONS:

For all motorcycles and ATVs utilizing transmissions without wet-clutches, differentials with or without hypoid gears and shaft-drives recommending 90wt gear oil. Not for use in transmissions with wet-clutches.

TECHNICAL DATA

SPECIFICATION	TEST METHOD	80W-90
APPEARANCE	VISUAL	Amber
VISCOSITY @ 40°C (cSt)	D445	171.7
VISCOSITY @ 100°C (cSt)	D445	16.3
VISCOSITY INDEX	D2270	99
FLASH POINT (°C)	D92	203
POUR POINT (°C)	D97	-27
DENSITY @ 15 °C (g/ml)	D4052	0.883

Maxima Racing Oils 9266 Abraham Way • Santee, CA 92071 USA **Phone** +1 (619)-449-5000 **Fax** +1 (619)-619-9694 **Web** www.MaximaUSA.com