Technical Data Sheet

RACING FORK FLUID

HIGH PERFORMANCE RACING FORK OIL

DESCRIPTION:

Mineral based racing fork oil designed for all high performance cartridge and standard-type forks. Shear stable, high viscosity index formulation maintains film strength and utilizes industry-leading anti-wear chemistry to reduce wear. Advanced, proprietary additive system prevents stiction and reduces running friction while minimizing foaming and air entrainment. Ultra clean formulation eliminates corrosion and conditions seals.

FEATURES & BENEFITS:

- Designed for high performance applications
- Reduces overall friction and prevents stiction
- Shear stable, high viscosity index formula maintains film strength and eliminates wear
- Maintains optimal damping performance by minimizing foaming and air entrainment
- Keeps internals clean while eliminating corrosion and conditioning seals

APPLICATIONS:

For all modern off-road and on-road upside down forks. Also for most late model applications with standard fork applications.

TECHNICAL DATA

SPECIFICATION	TEST METHOD	5WT	7WT	10WT	15WT
APPEARANCE	VISUAL	Green	Blue	Amber	Orange
VISCOSITY @ 40°C (cSt)	D445	16.2	26.7	37.4	47.1
VISCOSITY @ 100°C (cSt)	D445	4.4	5.4	7.7	8.5
VISCOSITY INDEX	D2270	201	139	182	159
FLASH POINT (°C)	D92	168	191	202	210
POUR POINT (°C)	D97	-33	-27	-24	-24
DENSITY @ 15 °C (g/ml)	D4052	0.863	0.869	0.866	0.871

Maxima Racing Oils 9266 Abraham Way • Santee, CA 92071 USA **Phone** +1 (619)-449-5000 **Fax** +1 (619)-619-9694 **Web** www.MaximaUSA.com